











| | | | Saga |
|---|-----------------|------------------|--|
| DESCRIPTION | | | |
| Total thickness | EN 428 | mm | 5,5 |
| Thickness of wearlayer | EN 429 | mm | 0.85 |
| Weight | EN 430 | g/m ² | 5400 |
| Tile size | EN 427 | mm | 500 x 500 |
| Number of tiles per package | - | - | 12 |
| CLASSIFICATION | | | |
| Norm / Product specification | | | EN 651 |
| European classification | EN 685 | class | 34 |
| Fire rating | EN 13 501-1 | class | C _{fl} -s1 |
| Static electrical propensity | EN 1815 | kV | <2 |
| Slip resistance wet: ramp test with oil | DIN 51130 | class | R9 |
| PERFORMANCE | | | |
| Wear resistance | EN 660.1 | mm | ≤0.08 |
| Wear group | EN 651 | - | T |
| Dimensional stability | EN 434 | % | ≤0.25 |
| Residual indentation | EN 433 | mm | ≤0.30 |
| Impact sound insulation | EN ISO 717-2 | dB | 18 |
| Thermal conductivity | EN 12524 | W/(m.K) | 0,25 |
| Colour fastness | EN 20 105 - B02 | degree | ≥6 |
| Chemical products resistance | EN 423 | - | OK |
| Anti-bacterial and fungicidal treatment | - | - | Sanosol® |
| Surface treatment | - | - | Protecsol® |
| MARQUAGE CE | | | |
|  | EN 14041 | |     |

| | | | Saga |
|---|-----------------|------------------|--|
| DESCRIPTION | | | |
| Total thickness | EN 428 | mm | 5,3 |
| Thickness of wearlayer | EN 429 | mm | 1.00 |
| Weight | EN 430 | g/m ² | 5150 |
| Tile size | EN 427 | mm | 500 x 500 |
| Number of tiles per package | - | - | 12 |
| CLASSIFICATION | | | |
| Norm / Product specification | | | EN 651 |
| European classification | EN 685 | class | 34 |
| Fire rating | EN 13 501-1 | class | C _{fl} -s1 |
| Static electrical propensity | EN 1815 | kV | <2 |
| Slip resistance wet: ramp test with oil | DIN 51130 | class | R9 |
| PERFORMANCE | | | |
| Wear resistance | EN 660.1 | mm | ≤ 0.08 |
| Wear group | EN 651 | - | T |
| Dimensional stability | EN 434 | % | ≤0.25 |
| Residual indentation | EN 433 | mm | ≤0.30 |
| Impact sound insulation | EN ISO 717-2 | dB | 18 |
| Thermal conductivity | EN 12524 | W/(m.K) | 0.25 |
| Colour fastness | EN 20 105 - B02 | degree | ≥6 |
| Chemical products resistance | EN 423 | - | OK |
| Anti-bacterial and fungicidal treatment | - | - | Sanosol® |
| Surface treatment | - | - | Protecsoi® |
| MARQUAGE CE | | | |
|  | EN 14041 | |     |

DESCRIPTION

| | | | |
|-----------------------------|--------|------------------|-----------|
| Total thickness | EN 428 | mm | 5,5 |
| Thickness of wearlayer | EN 429 | mm | 1.00 |
| Weight | EN 430 | g/m ² | 5330 |
| Tile size | EN 427 | mm | 500 x 500 |
| Number of tiles per package | - | - | 12 |




CLASSIFICATION

| | | | |
|------------------------------|-------------|-------|---------------------|
| Norm / Product specification | - | - | EN 651 |
| European classification | EN 685 | class | 34 - 42 |
| Fire rating | EN 13 501-1 | class | C _{fl} -s1 |
| Static electrical propensity | EN 1815 | kV | < 2 |

PERFORMANCE

| | | | |
|---|-----------------|---------|------------|
| Wear resistance | EN 660.1 | mm | ≤ 0.08 |
| Wear group | EN 651 | - | T |
| Dimensional stability | EN 434 | % | ≤ 0.25 |
| Residual indentation | EN 433 | mm | ≤ 0.30 |
| Impact sound insulation | EN ISO 717-2 | dB | 18 |
| Thermal conductivity | EN 12524 | W/(m.K) | 0,25 |
| Colour fastness | EN 20 105 - B02 | degree | ≥ 6 |
| Chemical products resistance | EN 423 | - | OK |
| Anti-bacterial and fungicidal treatment | - | - | Sanosol® |
| Surface treatment | - | - | Protecsol® |

CE MARKING

| | | | |
|--|----------|---|---|
|  | EN 14041 | - |  |
| | | - |  |